YAMASAKI 100G QSFP28 to 4 SFP28 Passive 30AWG DAC Cable

100G QSFP+28 to 4 SFP28 30AWG DAC Cable

YAMASAKI
Optical Technology

Powerful and Easy to use.

100G QSFP28 to 4 SFP28 Passive 30AWG Direct Attach Copper Twinax Cable is meticulously designed for high-performance and reliability. This 30AWG Passive Direct Attach Copper (DAC) cable provides robust, high-bandwidth connections, making it ideal for modern data centers, enterprise networks, and high-performance computing environments.

The Yamasaki 100G QSFP28 to 4 SFP28 Passive 30AWG Direct Attach Copper Twinax Cable are compliant with the QSFP28 to 4SFP28 MSA specifications.

Features:

-Hot-pluggable form-factor connectors

-Supports up to 100Gb/s to 4x 25G Data Rates

-Single 3.3V Power Supply and Industry Low Power dissipation

-Operating Temperature: 0 to 70°C

-Compliant - QSFP28 to 4SFP28 MSA Specification

-Low power consumption

-ROHS compliant (lead free)

Application:

-Network Communication
-FTTH/FTTB/FTTx
-ISB Backhaul Networking

YAMASAKI 100G to 4 SFP28 PASSIVE 30AWG DAC

General Specifications	YWDC-QSFP28/4SFP28-Px/30
Data Channel Rate	100Gbps
Media	Copper
Operating Temperature	0~70℃
Supply Voltage	3.3V nominal
Formfactor	QSFP28 to 4SFP28

Ordering Code:	Description:
YWDC-QSFP28/4SFP28-P0.5/30	100G QSFP28 to 4 SFP28 Passive 30AWG DAC Twinax Cable

YAMASAKI
Optical Technology

More information and details visit
www.yamasakiot.com

Specifications and descriptions are
subject to change without prior notice.

To contact us, please email:
sales@yamasakiot.com